

**INNOVATIVE MANUFACTURERS OF AWARD
WINNING FASTANKS, PORTABLE CONTAINMENT
TRUSTED WORLDWIDE**

A flexible solution to the permanent or temporary containment of liquids.

Applications



- Oil spill clean up / decontamination pool
- Effluent containment
- Water storage and treatment
- Emergency Relief aid
- Fire Fighting Water Dump
- Laboratory demonstration/mixing tank

Benefits



7500, 10,000 Litres

- Simple assembly in 10 minutes without tools
- Easy to transport, low packaged weight & volume
- Suitable for all climates
- Corrosion resistant, long storage life
- Multi-purpose use - Environmental protection, water or waste liquid storage
- Adapts to uneven ground
- Easy to clean



Supplied in an EzeBOX™

Specification

FASTANK	1500	2000
Assembled	3.2 dia x 1.15m h 126 dia x 45" h	3.2 dia x 1.5m h 126 dia x 60" h
Packaged Size	1.6 x 0.46 x 0.5m h 63 x 18 x 20" h	1.6 x 0.46 x 0.5m h 63 x 18 x 20" h
Packaged Weight	56 kg (123 lbs)	64 kg (141 lbs)
Capacity	7500 Litres 1500 Imp Gls 1800 US Gal	10000 Litres 2000 Imp Gls 2400 US Gal

Manufactured to ISO 9001 2015 Quality standard from (900gsm) rip stop acrylic & vinyl coated polyester.

Structural aluminium frame with either pressure die case aluminium or glass nylon filled joints.

Temp Range -30°C to +70°C.
UV Resistant.

Add-Ons Available:

- Ground Mat
- Roof Cover
- Polythene liner
- Decanting valve
- Pipe Saddle
- Pipe Kit, Tapstand
- Hand Pump

Please see overleaf>>

UK Patent No: 2524070

A Division Of:-



FAST
ENGINEERING

Contact the FASTEAM on T: +44 (0)28 9442 8686 or E: sales@fastank.com

Fast Engineering Ltd, 5 Windmill Court, Antrim, N.Ireland, BT41 2TX

Specifications may vary due to our policy of constant improvement. © Fast Engineering Ltd.

**INNOVATIVE MANUFACTURERS OF AWARD
WINNING FASTANKS, PORTABLE CONTAINMENT**
TRUSTED WORLDWIDE



Ground Mat

- Provides extra protection on rough or sharp ground
- Made from heavy duty vinyl coated reinforced fabric
- Can be used to provide an additional washable work area

Hand Pump

- Output 110L/min
- Attaches easily to tank
- Includes 2m of suction hose & 5m of 38mm outlet hose



Roof cover

- Prevents evaporation, rain ingress and contamination
- Can be reversed for use as a rainwater catcher

Polythene liner

- Made from virgin food grade polythene
- Prevents cross contamination
- Minimises cleaning of tank after use
- Protects tank from aggressive liquids and chemicals



Decanting valve

- Oil / water separation; enables reduction in the volume of stored liquid, thus reduced disposal & transport cost
- Adjustable flow rate
- Drain Valve

Pipe Kit

- Connects to reinforced wall
- Provide inlet, outlet, overflow and aeration options



Pipe Saddle

- 75mm (3") or 50mm (2")
- Simple to attach - no tools
- Safely pump over the tank wall

FASTAP Tap Stand

- Distribution of drinking water during emergencies
- 6 flexible outlets
- Factory tested, no leaks
- UK Patent No. GB2499726

