

**INNOVATIVE MANUFACTURERS OF AWARD
WINNING FASTANKS, PORTABLE CONTAINMENT
TRUSTED WORLDWIDE**

A portable water dam for firefighters.

Applications



- Fire services
- Storage of foam or firefighting additives
- Water dump in remote areas
- Water supply for work camps
- Liquid pollution storage
- Emergency containment

Benefits



- Simple assembly, no tools required
 - Suitable for a wide range of climates
 - Yellow collar clearly visible from air making it easier for pilot to accurately bullseye dipping bucket
 - Corrosion resistant
 - Multi-purpose use
 - Adapts to uneven ground
 - Easy to transport and clean
- Supplied in an Ezeebox™



Specification

FASTANK	FIREFIGHTER
Assembled	3.2 dia x 1.5m h (126 dia x 59" h)
Packaged	1.6 x 0.46 x 0.5m h (63 x 18 x 20" h)
Weight	64 kg (141 lbs)
Capacity	10000 Litres (2000 Imp Gls) (2400 US Gal)

Manufactured to ISO 9001 2015 Quality standard from (900gsm) rip stop acrylic and vinyl coated polyester fabric.

Structural aluminium frame glass nylon filled joints.

Temp Range -30°C to +70°C.
UV Resistant.

Add-ons Available

- Ground mat
- Hand pump
- Roof cover
- Polythene liner
- Decanting valve
- Pipe kit
- Action bag, Pipe saddle

Please see overleaf>>

UK Patent No: 2524070

A Division Of:-



FAST
ENGINEERING

Contact the FASTEAM on T: +44 (0)28 9442 8686 or E: sales@fastank.com

Fast Engineering Ltd, 5 Windmill Court, Antrim, N.Ireland, BT41 2TX

Specifications may vary due to our policy of constant improvement. © Fast Engineering Ltd.

**INNOVATIVE MANUFACTURERS OF AWARD
WINNING FASTANKS, PORTABLE CONTAINMENT
TRUSTED WORLDWIDE**



Ground Mat

- Provides extra protection on rough or sharp ground
- Made from heavy duty vinyl coated reinforced fabric
- Can be used to provide an additional washable work area

Hand Pump

- Output 110L/min
- Attaches easily to tank
- Includes 2m of suction hose & 5m of 38mm dia outlet hose



Roof cover

- Reduces evaporation, rain ingress and contamination
- Can be reversed for use as a rainwater catcher

Polythene liner

- Made from virgin food grade polythene
- Prevents cross contamination
- Minimises cleaning of tank after use
- Protects tank from aggressive liquids



Decanting Valve

- Oil / water separation; enables reduction in volume of stored liquid, thus reduced disposal & transport cost
- Adjustable flow rate

Pipe Kit

- Connects to reinforced wall
- Various fittings enable inlet, outlet, overflow and aeration options



Pipe Saddle

- 75mm (3") or 50mm (2")
- Simple to attach - no tools.
- Safely pump over tank wall

Action Bag

- Soft and lightweight carrying case
- 6 webbed handles
- Heavy duty zips
- Made from yellow waterproof fabric

