

**INNOVATIVE MANUFACTURERS OF AWARD  
WINNING FASTANKS, PORTABLE CONTAINMENT  
TRUSTED WORLDWIDE**

## Emergency Containment & Washdown.

### Applications



- Oil spill clean up/decontamination pool
  - Over-splash protection
  - Containment of leaks
  - Animal rescue enclosure
  - Liquid storage
  - Soiled sorbant storage
- Supplied in carry bag



### Benefits



- Simple assembly, no tools required
- Low packaged volume and weight
- Corrosion resistant
- Quick to set up
- Easy to clean
- Multi purpose uses
- Can be hand carried



### Specifications

FASTANK	RAPIDE
Assembled	1.72 x 1.67 x 0.6m (68 x 66 x 24")
Packaged	1.75 x 0.23 x 0.18m (69 x 9 x 7")
Weight	15 kg (33 lbs)
Capacity	1500 Litres (1.5m³) (330 Imp Gal.)

Manufactured to ISO 9001 2015 Quality Standard from (900gsm) rip stop acrylic and vinyl coated polyester fabric.

Structural aluminium frame & joins.  
Stainless steel fittings.

Temp Range -30°C to +70°C.  
UV Resistant.

#### Add-ons Available

- Ground mat
- Hand pump
- Roof cover
- Polythene Liner
- Decanting valve
- Pipe Kit
- Pipe saddle, Foot plates
- Anti-slip mat, Support Bars

Please see overleaf>>

A Division Of:-



**FAST**  
ENGINEERING

Contact the FASTEAM on T: +44 (0)28 9442 8686 or E: [sales@fastank.com](mailto:sales@fastank.com)

Fast Engineering Ltd, 5 Windmill Court, Antrim, N.Ireland, BT41 2TX

Specifications may vary due to our policy of constant improvement. © Fast Engineering Ltd.

**INNOVATIVE MANUFACTURERS OF AWARD  
WINNING FASTANKS, PORTABLE CONTAINMENT  
TRUSTED WORLDWIDE**



### Ground Mat

- Provides extra protection on rough or sharp ground
- Made from heavy duty vinyl coated reinforced fabric
- Can be used to provide an additional washable work area

### Hand Pump

- Output 110L/min
- Attaches easily to tank
- Includes 2m of suction hose & 5m of 38mm dia outlet hose



### Roof cover

- Reduces evaporation, rain ingress and contamination
- Can be reversed for use as a rainwater catcher

### Polythene liner

- Virgin food grade polythene
- Prevents cross contamination
- Minimises cleaning of tank after use



### Decanting Valve

- Oil / water separation; enables reduction in volume of stored liquid, thus reduced disposal & transport cost
- Adjustable flow rate
- Connects to reinforced wall
- Various fittings enable inlet, outlet, overflow and aeration options



### Pipe Kit



### Pipe Saddle

- 75mm (3") or 50mm (2")
- Simple to attach - no tools
- Safely pump over the tank wall

### Foot plates

- For use on soft ground
- Easily attached- no tools
- Size 133mm<sup>2</sup> (5") square



### Anti Slip Mat

- Prevents slippage of persons or objects in the tank
- Protects base of tank from damage

### Support Bars

- Sold as a pair
- Corrosion resistant
- Forms a work platform or support for equipment

